

# MOSO® - WOCA project maintenance & care instruction

for MOSO® Bamboo UltraDensity® flooring in large areas



## Preparation:

It is important for the oil that the room and the floor are at a temperature between 15°C and 30°C and the air humidity is approximately 50%. The moisture content on the surface must not exceed 12%. Make sure that the room is well ventilated for optimal evaporation and drying time.

## Regular Cleaning (frequency at your own discretion)

For regular cleaning, use WOCA Commercial Soap:

**Step 1)** Mix WOCA Commercial Soap on a 1:40 ratio with lukewarm water (for example: 0,25 liter Commercial Soap to 10 liter water) and pour it in the scrubber dryer reservoir.

**Step 2)** Clean the floor parallel to the bamboo grain using a floor washing machine/scrubber dryer (see examples on the right). By moving lengthwise, the least amount of liquid (including dirt) remains on the surface and thorough drying will be fast.

If cleaning is done sufficiently (often) there will be less need to treat/oil the floor again, as WOCA Commercial Soap does not remove the oil protection. If regular cleaning is not sufficient, proceed with 'Intensive Cleaning'.



'walk behind' machine



'ride-on' machine



'Commercial Soap'

## 2-in-1 Treatment (if regular cleaning is no longer sufficient)

In a 2-in-1 treatment using WOCA Commercial Oil, deep cleaning and oiling of the surface can be done in one single process. This is especially convenient in high traffic areas, because the required time for the maintenance is limited. Before starting this treatment, make sure to remove stubborn dirt. In case of stubborn dirt, use WOCA Intensive Cleaner prior to using Commercial Oil. If cleaning is done sufficiently (often) and the floor is free of dirt, Commercial Oil can be applied directly.

**Step 1)** Shake the container of Commercial Oil thoroughly.

**Step 2)** Apply approximately 100 ml of WOCA Commercial Oil per 10-20 m<sup>2</sup>. Apply the oil using a polishing machine and a green polishing pad. Continue polishing until the bamboo is saturated and the surface has an even, uniform appearance. The surface must not be wet afterwards.



'Commercial Oil'



**Please note:** cloths/pads that have been soaked in oil can self-ignite if disposed incorrectly. For proper disposal, cloths/pads should therefore be stored in a tightly-sealed container full of water immediately after use.



'Polishing machine'

## Intensive cleaning (if 2-in-1 treatment does not help)

If the surface is very dirty, we recommend cleaning with WOCA Intensive Wood Cleaner:

**Step 1)** Mix WOCA Intensive Wood Cleaner on a 1:20 ratio with lukewarm water (for example: 0,5 liter Intensive Wood Cleaner to 10 liter water) and pour it in the scrubber dryer reservoir.

**Step 2)** Wash the floor parallel to the bamboo grain using a scrubber dryer on low forward speed allowing the Intensive Wood Cleaner to dissolve dirt. If the bamboo is very dirty, repeat this step .

**Step 3)** Let the surface dry completely before protecting it again with WOCA Commercial Oil.



'Intensive Wood Cleaner'

WOCA Intensive Wood Cleaner is a heavy-duty, deep cleaner; therefore, surfaces should be re-oiled after this treatment.